


GENERAL NOTES

1. STAMPED CONCRETE PAVEMENT TO BE CREATED USING RAILROAD STAMP. PRODUCT NUMBER BST8900 (WWW.BUTTERFIELDCOLOR.COM)
2. COLORS FOR STAMPED CONCRETE TO BE AS MANUFACTURED BY BUTTERFIELD COLOR IN THE "ELEMENT" COLOR FAMILY AS FOLLOWS:
 COLOR 1 - RAILROAD TIMBERS TO BE BAS-19, KONA BROWN.
 COLOR 2 - RAIL TRACKS TO BE BAS-18, WEATHERED BRONZE.
 COLOR 3 - STONE BALLAST TO BE ELE-128, GRAY
3. A LIQUID RELEASE AGENT IS APPLIED TO THE STAMP PRIOR TO USING AND THROUGHOUT THE STAMPING PROCESS CALLED "PERMA-CAST CLEAR LIQUID RELEASE".
 WWW.BUTTERFIELDCOLOR.COM/PRODUCT-CATEGORY/ANTIQUING-AND-RELEASE-AGENTS
4. AFTER CONCRETE CURE, THE AREA IS REQUIRED TO BE POWER WASHED TO REMOVE ANY RELEASE AGENT AND ALLOWED TO DRY PRIOR TO COLOR APPLICATION.
5. AFTER CURING OF COLOR AGENT, APPLY "CLEAR GROUND-CURE AND SEAL" TO FINISHED CONCRETE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATION. WWW.BUTTERFIELDCOLOR.COM/PRODUCT-CATEGORY/CURING-AND-SEALING.
6. BUTTERFIELD COLOR CONTACT INFORMATION:
 NASHVILLE POWER RENTAL AND SALES
 HTTPS://PRSCONCRETE.COM
 615-837-1450
7. DESIRABLE SIDEWALK CROSS SLOPE IS 1.5%, ABSOLUTE MAXIMUM IS 2.0%.
8. EXPANSION JOINTS SHALL BE PLACED AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER. ISOLATION/EXPANSION JOINTS SHALL BE: RUBBERIZED EXPANSION JOINT FILLER (AASHTO M153, TYPE 1)
9. 4" MIN BASE STONE (303-01 MINERAL AGGREGATE, TYPE "A" BASE, GRADING "D" REQUIRED UNDER ALL SIDEWALKS.



**INTERURBAN RAILWAY DECORATIVE
STAMPED CONCRETE TRAIL**

CITY OF FRANKLIN
NOT TO SCALE

CITY
ENGINEER:

Paul P. Hoge

DATE:
03/20/2023

DWG. NO.

CS11