


PAVEMENT SCHEDULE

- ① **SPORT SURFACE**
 - 2 COATS OF SQUEEGEE APPLIED SPORTMASTER ACRYLIC COLOR CONCENTRATE.
 - APPLY ONE COAT OF SPORTS MASTER STRIPE RITE FOR ALL WHITE EDGE LINES.
 - APPLY TEXTURED ACRYLIC WHITE PLAYING LINES (BASE LINE SHALL BE 4" AND ALL OTHERS SHALL BE 2") USING SPORT MASTER TEXTURED WHITE LINE PAINT.
 - COURT COLOR SHALL BE LIGHT BLUE, BORDER SHALL BE LIGHT GREEN.
- ② 1.5" – BITUMINOUS SURFACE COURSE
411-01.11 ACS MIX(PG64-22) GRADING E RDWY
- ③ TACK COAT
403-01 BITUMINOUS MATERIAL FOR TACK COAT (TC) @0.07 GAL/SY
- ④ 2" – BITUMINOUS AGGREGATE BASE
307-01.08 ASPHALT CONCRETE MIX (PG64-22)(BPMB-HM) GRADING B-M2
- ⑤ PRIME COAT
402-01 BITUMINOUS MATERIAL FOR PRIME COAT (PC) @0.30-0.35 GAL/SY
402-02 AGGREGATE FOR COVER MATERIAL (PC) @8-12LBS/SY
- ⑥ 8" MINERAL AGGREGATE BASE 303-01 MINERAL
303-01 MINERAL AGGREGATE, TYPE "A" BASE, GRADING"D"

GENERAL NOTES

- 1) ASPHALT COURTS SHALL BE SLOPED IN A TRUE PLANE A MIN OF 0.83% TO A MAXIMUM OF 1.00%
- 2) THE FINISHED COURT SHALL NOT VARY MORE THAN $\frac{3}{8}$ " FROM THE DESIGNED ELEVATION WITHIN THE PRIMARY PLAYING AREA. THE SURFACE SHALL NOT VARY MORE THAN $\frac{1}{4}$ " IN 10' WHEN MEASURED IN ANY DIRECTION USING A STRAIGHTEDGE.
- 3) PAVEMENT SURFACE MUST BE CLEANED ENTIRELY OF DUST, DIRT, DEBRIS AND ALL LOOSE MATERIALS, AND NEW ASPHALT MUST CURE 30 DAYS BEFORE APPLICATION OF SPORT SURFACE.
- 4) COLD JOINTS ON THE ASPHALT MAT SHALL NOT BE ALLOWED.



TENNIS COURT PAVEMENT SECTION

CITY OF FRANKLIN
NOT TO SCALE

CITY
ENGINEER:

Paul P. Hoyle

DATE:
03/20/2023

DWG. NO.

CS30